



468F57



54DE08



411Z76



Rectangular LED Headlights

Headlamps offer LED technology in configurations to suit most on-road vehicles.

Volt Bulb	Current Rating	No. of Bulbs	Lumens	Termination Type	Mounting Type	Color	Fits	L	H	W	D	Brand	Mfr. Model	Item No.
Low Beam 5x7														
12 to 24V	1.94 to 0.16 A	0	975 lm, 1,200 lm	H4		White	Universal	7 7/8 in	5 19/32 in	7 7/8 in	—	J.W. Speaker	8900 Evo 2	468F57
Low Beam 4x6														
10 to 32V	2.25 A	5	2,830 lm	Pigtail	Recessed	Gray	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 1/4 in	3 27/64 in	J.W. Speaker	8800 Evolution 2	52XE89
10 to 32V	2.25 A	5	2,830 lm	Pigtail	Recessed	Black	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 1/4 in	3 27/64 in	J.W. Speaker	8800 Evolution 2	52XE93
12 to 24V	0.6 A	1	400 lm	H4 Pigtail	Surface	Black	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 3/4 in	3 9/64 in	Maxxima	VHL-4X6L0	54DE08
9 to 30V	0.61 A	1	630 lm	Automotive H4	Recessed	Clear	Motorcycles, Passenger and Commercial Vehicles	6 1/2 in	4 1/8 in	2 3/4 in	2 7/8 in	Grote	94421-5	411Z76
High Beam 4x6														
10 to 32V	2.25 A	3	2,250 lm	Pigtail	Recessed	Black	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 1/4 in	3 27/64 in	J.W. Speaker	8800 Evolution 2	52XE94
10 to 32V	2.25 A	3	2,250 lm	Pigtail	Recessed	Gray	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 1/4 in	3 27/64 in	J.W. Speaker	8800 Evolution 2	52XE90
12 to 24V	0.7 A	1	400 lm	H4 Pigtail	Surface	Black	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 3/4 in	4 19/64 in	Maxxima	VHL-4X6HI	54DE11
High/Low Beam 5x7														
9 to 32V	2.54 A	1	361 lm, 886 lm	3 Pin H4 Connector	Recessed	Clear	Motorcycles, Passenger and Commercial Vehicles	8 in	5 1/2 in	4 in	4 7/32 in	Grote	90951-5	411Z74
DRL/Low Beam Combo 4x6														
12 to 24V	0.6 A	5	400 lm	H4 Pigtail	Surface	Black	Car, Trailer, Truck, Van	6 1/2 in	4 1/4 in	3 3/4 in	4 19/64 in	Maxxima	VHL-4X6DRL	54DE10
12 to 24V	5.35 to 1.32 A	0	975 lm, 1,200 lm	H4		Black	Universal	7 7/8 in	5 19/32 in	7 7/8 in	—	J.W. Speaker	8910 Evo 2	468F60



52XE91



52XE96

Heated LED Rectangular Headlights



LED headlights have a thermally conductive grid that deices lenses in response to the ambient temperature, to help improve visibility without requiring action by the driver. Headlights feature improved light output, glare reduction, and light placement to meet the demands of on-road trucking. The tough, die-cast housing offers protection from salt spray for efficient thermal management.

Current Rating	Volt Bulb	No. of Bulbs	Wiring Connection	Mounting	Used For	L	W	D	Chrome Item No.	Black Item No.	White Item No.
Low Beam											
2.25 A	10 to 32V	5	Hardwired	Permanent	Cars, Trucks, Vans	6 1/2 in	3 1/4 in	4 in	52XE91	52XE95	—
High Beam											
2.25 A	10 to 32V	3	Hardwired	Permanent	Cars, Trucks, Vans	6 1/2 in	3 1/4 in	4 in	52XE92	52XE96	—
Headlight											
5.35 to 1.32 A DC	12 to 24V	0	H4 Connector	Recessed	Cars, Trucks, Vans	7 7/8 in	7 7/8 in	—	—	—	468F59



Replacement Headlights

Trade No.	Voltage	Watts	Average Life	Item No.
Fog Lights				
880	12V AC	27W	300 hr.	2FMU6
881	12V AC	27W	300 hr.	2FMU7
885	12V AC	50W	200 hr.	2EKW1
886	12V AC	50W	200 hr.	2FMU8
889	12V AC	27W	300 hr.	2FMU9
890	12V AC	27W	300 hr.	2FMV1
893	12V AC	37.5W	200 hr.	2EKW3
894	12V AC	37.5W	200 hr.	2FMV3
896	12V AC	37.5W	200 hr.	2FMV4
898	12V AC	37.5W	1900 hr.	2FMV5
9008	12/12V AC	55/60W	200/600 hr.	2FMV5
9055	12/12V AC	55W	800 hr.	2FMV8
9140	12V AC	40W	1200 hr.	2FMV9
9145	12V AC	45W	1000 hr.	2FMZ1
H2	12.8V AC	55W	255 hr.	2FNC8
	12V AC	130W	50 hr.	2FND1
	12.8V AC	100W	150 hr.	2FNC9
H3	12.8V AC	55W	400 hr.	2FND2
	13.5V AC	55W	400 hr.	2FND3
	24V AC	84W	400 hr.	2FND4
H8	12V AC	35W	350 hr.	2FND8

Trade No.	Voltage	Watts	Average Life	Item No.
High/Low Beam				
9003	12V AC	61/67W	150/320 hr.	2EKW8
9004	12/12V AC	45/65W	150/320 hr.	2FMY1
	12V AC	45/65W	300/640 hr.	2FNA8
9007	12/12V AC	55/65W	150/320 hr.	2FMY4
	12V AC	55/65W	300/1200 hr.	3EHN9
H4	13.2V AC	100W	75/150 hr.	2FND5
	13.2V AC	55/60W	150/300 hr.	2EKX5
H7	28V AC	70/75W	150/300 hr.	2EKX6
	12V AC	55W	250 hr.	2FND6
H7	12V AC	55W	500 hr.	2FND7
High Beam				
9005	12V AC	65W	150 hr.	2FMY2
	12V AC	65W	320 hr.	2FNA9
H9	12V AC	65W	500 hr.	3EHN7
	12V AC	65W	200 hr.	2FND9
H9	12V AC	65W	300 hr.	2FNE1
Low Beam				
9006	12V AC	55W	200 hr.	29VJ55
	12V AC	55W	320 hr.	2FNB1
	12V AC	55W	320 hr.	2FMY3
H3	12V AC	65W	200 hr.	2EKX3
	24V AC	84W	300 hr.	2FNC5
H11	12V AC	55W	600 hr.	2FNC6
	12V AC	55W	1000 hr.	2FNC7
Tractor				
862	12V AC	37.5W	1900 hr.	2EKV8