



7800 SERIES

- Converts to a step or extension ladder
- Step ladder height: 4XN76 is 6 ft, 41D279 is 7 ft, 4XN77 is 8 ft
- Padded V-rung at top in extension position
- Fixed aluminum locks secure rungs in extension ladder position
- Large hoop feet

Fiberglass, Combination Ladder, Type IAA, 375-lb. Duty Rating



D7100-2LV SERIES

- Rung plate rung to rail connections
- Base and fly separate easily
- Factory installed, foot action Level Lok extends up to 10" in 3/8" increments
- Prepierced holes at top of fly section for easy field installation of accessories
- 36-ft. and 40-ft. models are Type 1A, 300 lb.

Fiberglass, D-Rung Extension Ladder, Type IAA, 375-lb. Duty Rating



D8200-2EQ SERIES

- Factory installed EverLevel leveling system: adjusts up to 8 1/4" in 3/8" increments
- Direct rung to rail connections
- Dual-action feet with spur plate

Fiberglass, D-Rung Extension Ladder, Type IA, 300-lb. Duty Rating



Specialty Extension and Straight Ladders

- Exclusive ALFLO rung joint connections for twist-proof performance except 9500 Series
- Slip-resistant Traction-Tred rungs
- Mar-resistant end caps

Series	Industry Ladder Size	Extended Ladder Height	Material	Item No.
Step/Extension				
Type IAA, 375 lb Duty Rating				
7800	—	12 ft	Fiberglass	4XN76
	—	12 ft		41D279
	—	16 ft		4XN77

Extension				
Type IAA, 375 lb Duty Rating				
D7100-2LV	20 ft	17 ft	Fiberglass	3AZT2
	24 ft	21 ft		3AZT3
	28 ft	25 ft		3AZT4
	32 ft	29 ft		41D254

Type IA, 300 lb Duty Rating				
D8200-2EQ	20 ft	17 ft	Fiberglass	41D268
	24 ft	21 ft		41D269
	28 ft	25 ft		41D270

Type I, 250 lb Duty Rating				
560-3	60 ft	47 ft	Aluminum	4XN68
	16 ft	13 ft		1FCF6
	20 ft	17 ft		1FCF7
	24 ft	21 ft		1FCF8
D1800-2EQ	24 ft	21 ft	Aluminum	1FCF9
	28 ft	25 ft		1FCF9

Series	Ladder Height	Top Step Height	Material	Item No.
Straight				
Type IAA, 375 lb Duty Rating				
500-1	10 ft	10 ft	Aluminum	41D309
	12 ft	12 ft		41D310
	14 ft	14 ft		41D311
	16 ft	16 ft		41D312
7100-1	8 ft	8 ft	Fiberglass	41D263
	10 ft	10 ft		41D264
	12 ft	12 ft		41D265
	14 ft	14 ft		41D266
	16 ft	16 ft		41D267
	8 ft	4 ft		3AZV4
M7100-1	10 ft	6 ft	Fiberglass	3AZV5
	12 ft	8 ft		3AZV6
	14 ft	10 ft		3AZV7
	16 ft	12 ft		3AZV8

Type IA, 300 lb Duty Rating				
500-1	20 ft	20 ft	Aluminum	41D314
	24 ft	24 ft		41D315
	8 ft	4 ft		3AZU7
	10 ft	6 ft		3AZU8
D1500-1	12 ft	8 ft	Aluminum	3AZU9
	14 ft	10 ft		3AZV1
	16 ft	12 ft		3AZV2
	18 ft	14 ft		3AZV3
	20 ft	20 ft		41D316
	8 ft	4 ft		2EJG2
D6200-1	10 ft	6 ft	Fiberglass	2EJG3
	12 ft	8 ft		2EJG4
	14 ft	10 ft		2EJG5
	16 ft	12 ft		2EJG6
	20 ft	16 ft		2EJG7

Sectional				
Type I, 250 lb Duty Rating				
S7700	6 ft	6 ft	Fiberglass	41D284



560-3 SERIES

- Removable top fly section
- Heavy-duty rope and double pulley system
- Dual-action feet with spur plate
- Maximum working length is 47 ft.

Aluminum, Round Rung Extension Ladder, Type I, 250-lb. Duty Rating



D1800-2EQ SERIES

- Factory installed EverLevel leveling system: adjusts up to 8 1/4" in 3/8" increments
- Direct rung to rail connections
- Built-in bubble leveler at bottom rung
- Dual-action feet with spur plate

Aluminum, D-Rung Extension Ladder, Type I, 250-lb. Duty Rating



500-1 SERIES

- Dual-action feet with spur plate
- Hoop end caps
- 8-ft. to 12-ft. ladders are 16 7/8"W
- 24-ft. ladder is 20 7/8"W
- 18-ft., 20-ft. and 24-ft. models are Type IA, 300 lb.

Aluminum, Round Rung Straight Ladder, Type IAA, 375-lb. Duty Rating



7100-1 SERIES

- Rung plate rung to rail connections
- Rail shield and shoe bracket protect rail
- Dual-action feet with spur plate for use on hard or penetrable surfaces

Fiberglass, Round Rung Straight Ladder, Type IAA, 375-lb. Duty Rating



M7100-1 SERIES

- Round shaped rungs
- 3-ft. replaceable plastic sleeves to avoid rim damage to rail
- Ladder is 12 3/8"W
- Wide hoop feet with rubber pads at bottom

Fiberglass, Manhole Ladder, Type IAA, 375-lb. Duty Rating



D1500-1 SERIES

- Dual-action feet with spur plate for use on hard or penetrable surfaces
- Mar-resistant end caps
- Ladder is 18 1/8"W

Aluminum, D-Rung Straight Ladder, Type 1A, 300-lb. Duty Rating



D6200-1 SERIES

- Dual-action feet with spur plate for use on hard or penetrable surfaces
- Molded rung braces at bottom for increased durability
- Ladder is 19"W

Fiberglass, D-Rung Straight Ladder, Type IA, 300-lb. Duty Rating



S7700 SERIES

- Ideal for manhole use
- Maximum number of 3 sections can be used, each section 6-ft. high
- Lock sections with cam driven tension clamps
- Ladder width 12"
- Requires Shoe 41D286 and End Cap 41D285, available separately

Fiberglass, Parallel Sectional Ladder, Type I, 250-lb. Duty Rating