



Find more information on Rolling Ladders on page 995.

4-Step
4XM72



Cotterman® Welded Aluminum Rolling Ladders

- Ship assembled
- 350-lb. load capacity
- 14" platform depth
- 59° climbing angle

Up to 50% lighter than comparable steel ladders, aluminum is easy to clean and corrosion-resistant.

| Platform Height | Overall Height | No. of Steps | Platform Width | Bottom Width | Step Lock Actuation | Base Depth | SERRATED Item No. | RIBBED Item No. |
|----------------------------|----------------|--------------|----------------|--------------|---------------------|------------|-------------------|-----------------|
| With 30"H Handrails | | | | | | | | |
| 20 in | 50 in | 2 | 16 in | 18 in | Step | 23 in | 2JYW3 | — |
| | 50 in | 2 | 24 in | 26 in | Step | 23 in | 2JYX1 | — |
| 30 in | 60 in | 3 | 16 in | 22 in | Step | 29 in | 2JYW5 | 21VE75 |
| | 60 in | 3 | 24 in | 30 in | Step | 29 in | 4XM71 | 21VE76 |
| 40 in | 70 in | 4 | 16 in | 22 in | Step | 36 in | 2JYW7 | 21VE78 |
| | 70 in | 4 | 24 in | 30 in | Step | 36 in | 4XM72 | 21VE79 |
| 50 in | 80 in | 5 | 16 in | 22 in | Step | 43 in | 2JYW8 | 21VE80 * |
| | 80 in | 5 | 24 in | 30 in | Step | 43 in | 4XM73 | 21VE81 * |
| 60 in | 90 in | 6 | 16 in | 24 in | Step | 50 in | 2JYW9 | 21VE82 * |
| | 90 in | 6 | 24 in | 30 in | Step | 50 in | 4XM74 | 21VE83 * |
| 70 in | 100 in | 7 | 24 in | 30 in | Step | 57 in | 2JYX2 | 21VE84 * |
| 80 in | 110 in | 8 | 24 in | 30 in | Step | 63 in | 2JYX3 | 21VE85 * |
| Without Handrails | | | | | | | | |
| 12" | 12 in | 1 | 14 in | 26 in | Casters | 20 in | 20Z531 | — |
| 20" | 20 in | 2 | 14 in | 18 in | Casters | 23 in | 2JYW2 | — |
| | 20 in | 2 | 14 in | 26 in | Casters | 23 in | 20Z532 | — |
| 20 in | 20 in | 2 | 16 in | 18 in | Step | 23 in | 21VE71 | — |
| 30" | 30 in | 3 | 14 in | 22 in | Casters | 29 in | 2JYW4 | — |
| | 30 in | 3 | 14 in | 30 in | Casters | 29 in | 20Z533 | — |
| 30 in | 30 in | 3 | 16 in | 22 in | Step | 29 in | — | 21VE74 |
| 40 in | 40 in | 4 | 24 in | 30 in | Casters | 36 in | 20Z534 | 45CJ71 † |
| | 40 in | 4 | 16 in | 22 in | Casters | 36 in | 2JYW6 | 21VE77 † |

* Ladders for use in California will be modified to comply with California OSHA Standards.
† 4-step without handrails not for use in California.

6-Step
3FMJ2



Cotterman® Welded Stainless Steel Rolling Ladders

- Ship assembled
- 450-lb. load capacity
- 10" platform depth
- 59° climbing angle

Type 304 stainless steel construction is ideal for washdown and corrosive environments.

| Platform Height | Overall Height | No. of Steps | Platform Width | Bottom Width | Step Lock Actuation | Base Depth | Handrail Height | SERRATED Item No. | EXPANDED METAL Item No. |
|--------------------------|----------------|--------------|----------------|--------------|---------------------|------------|-----------------|-------------------|-------------------------|
| With Handrails | | | | | | | | | |
| 20 in | 50 in | 2 | 16 in | 18 in | Step | 19 in | 30 in | — | 45CH96 |
| | 60 in | 3 | 16 in | 20 in | Step | 27 in | 30 in | 45CJ01 | 45CH71 |
| 30 in | 60 in | 3 | 24 in | 30 in | Step | 27 in | 30 in | 45CJ49 | 45CJ73 |
| 40 in | 70 in | 4 | 16 in | 20 in | Step | 31 in | 30 in | 5FYP9 | 5FYR5 * |
| | 70 in | 4 | 24 in | 30 in | Step | 31 in | 30 in | 45CH55 | 45CH53 |
| 50 in | 80 in | 5 | 24 in | 30 in | Foot | 40 in | 30 in | 5FYR0 | 5FYR6 * |
| | 80 in | 5 | 16 in | 20 in | Foot | 39 in | 30 in | 45CJ04 | 45CJ06 * |
| 60 in | 90 in | 6 | 24 in | 30 in | Foot | 46 in | 30 in | 3FMJ2 | 5FYR7 * |
| | 90 in | 6 | 16 in | 24 in | Foot | 46 in | 30 in | 45CJ84 | 45CH94 * |
| 70 in | 100 in | 7 | 24 in | 30 in | Foot | 53 in | 30 in | 5FYR1 | 5FYR8 * |
| 80 in | 110 in | 8 | 24 in | 32 in | Foot | 58 in | 30 in | 3FMJ3 | 5FYR9 * |
| 90 in | 120 in | 9 | 24 in | 32 in | Foot | 65 in | 30 in | 5FYR2 | 5FYT0 * |
| 100 in | 130 in | 10 | 24 in | 32 in | Foot | 72 in | 30 in | 3FMJ4 | 5FYT1 * |
| 110 in | 140 in | 11 | 24 in | 32 in | Foot | 81 in | 30 in | 45CH60 | 45CJ47 * |
| 120 in | 162 in | 12 | 24 in | 32 in | Foot | 88 in | 42 in | 45CJ42 | 45CJ38 * |
| Without Handrails | | | | | | | | | |
| 20" | 20 in | 2 | 10 in | 18 in | Casters | 19 in | — | 5FYP7 | 5FYR3 |
| 30" | 30 in | 3 | 10 in | 20 in | Casters | 26 in | — | 5FYP8 | 5FYR4 |

* Ladders for use in California will be modified to comply with California OSHA Standards.



7-Step
4RCN5



7-Step
46C332

Cotterman® Heavy-Duty Steel Rolling Ladders



- Handrails available
- Ship unassembled
- 24" platform width
- 50° and 56° ladders are gray; 59° are gray/yellow
- Foot-activated step lock

50°, 56°, and 59° climbing angles for easy forward descent.

| Description | Brand | Item No. |
|---|-----------|----------|
| Gate Options for Extra Heavy-Duty Rolling Ladders | | |
| Front Gate | Cotterman | 29JU21 |
| Rear Side Gate | Cotterman | 29JU24 |

| Platform Height | Overall Height | No. of Steps | Load Capacity | Platform Depth | Bottom Width | Base Depth | Handrail Height | Brand | PERFORATED Item No. | SERRATED Item No. | EXPANDED METAL Item No. |
|--------------------|----------------|--------------|---------------|----------------|--------------|------------|-----------------|-----------|---------------------|---------------------|-------------------------|
| 50° Climbing Angle | | | | | | | | | | | |
| 60 in | 90 in | 6 | 800 lb | 12 in | 30 in | 60 in | 30 in | Cotterman | 3UU97 * | 5FZA2 * | 5FYZ3 * |
| | 90 in | 6 | 800 lb | 24 in | 30 in | 72 in | 30 in | Cotterman | 20Z444 * | 20Z443 * | 20Z442 * |
| | 96 in | 6 | 600 lb | 17 in | 35 in | 66 in | 36 in | Tri-Arc | 4RCN4 * | 4RCP2 * | — |
| 70 in | 100 in | 7 | 800 lb | 12 in | 30 in | 69 in | 30 in | Cotterman | 3UU98 * | 5FZA3 * | 5FYZ4 * |
| | 100 in | 7 | 800 lb | 24 in | 30 in | 81 in | 30 in | Cotterman | 20Z447 * | 20Z446 * | 20Z445 * |
| | 106 in | 7 | 600 lb | 17 in | 35 in | 74 in | 36 in | Tri-Arc | 4RCN5 * | 4RCP3 * | — |
| 80 in | 110 in | 8 | 800 lb | 12 in | 32 in | 78 in | 30 in | Cotterman | 3UU99 * | 5FZA4 * | 5FYZ5 * |
| | 110 in | 8 | 800 lb | 24 in | 32 in | 90 in | 30 in | Cotterman | 20Z450 * | 20Z449 * | 20Z448 * |
| | 116 in | 8 | 600 lb | 17 in | 35 in | 82 in | 36 in | Tri-Arc | 4RCN6 * | 4RCP4 * | — |
| 90 in | 120 in | 9 | 800 lb | 12 in | 32 in | 88 in | 30 in | Cotterman | 5FZC1 * | 5FZC3 * | 5FZC2 * |
| | 120 in | 9 | 800 lb | 24 in | 32 in | 100 in | 30 in | Cotterman | 20Z453 * | 20Z452 * | 20Z451 * |
| | 126 in | 9 | 600 lb | 17 in | 35 in | 91 in | 36 in | Tri-Arc | 4RCN7 * | 4RCP5 * | — |
| 100 in | 130 in | 10 | 800 lb | 12 in | 32 in | 97 in | 30 in | Cotterman | 3UU84 * | 5FZA5 * | 5FYZ6 * |
| | 130 in | 10 | 800 lb | 24 in | 32 in | 109 in | 30 in | Cotterman | 20Z456 * | 20Z455 * | 20Z454 * |
| | 136 in | 10 | 600 lb | 17 in | 35 in | 99 in | 36 in | Tri-Arc | 4RCN8 * | 4RCP6 * | — |
| 110 in | 140 in | 11 | 800 lb | 12 in | 32 in | 106 in | 30 in | Cotterman | 3UU85 * | 5FZA6 * | 5FYZ7 * |
| | 140 in | 11 | 800 lb | 24 in | 32 in | 118 in | 30 in | Cotterman | 20Z458 * | 20Z457 * | 20Z457 * |
| | 146 in | 11 | 600 lb | 17 in | 35 in | 107 in | 36 in | Tri-Arc | 4RCN9 * | 4RCP7 * | — |
| 120 in | 156 in | 12 | 600 lb | 17 in | 35 in | 116 in | 36 in | Tri-Arc | 4RCP1 * | 4RCP8 * | — |
| | 162 in | 12 | 800 lb | 12 in | 32 in | 116 in | 42 in | Cotterman | 3UU86 * | 5FZA7 * | 5FYZ8 * |
| | 162 in | 12 | 800 lb | 24 in | 32 in | 128 in | 42 in | Cotterman | 20Z462 * | 20Z461 * | 20Z460 * |
| 130 in | 172 in | 13 | 800 lb | 12 in | 42 in | 125 in | 42 in | Cotterman | 3UU87 * | 5FZA8 * | 5FYZ9 * |
| | 172 in | 13 | 800 lb | 24 in | 42 in | 137 in | 42 in | Cotterman | 20Z465 * | 20Z464 * | 20Z463 * |
| | 182 in | 14 | 800 lb | 12 in | 42 in | 134 in | 42 in | Cotterman | 3UU88 * | 5FZA9 * | 5FZA0 * |
| 140 in | 182 in | 14 | 800 lb | 24 in | 42 in | 146 in | 42 in | Cotterman | 20Z468 * | 20Z467 * | 20Z466 * |
| | 192 in | 15 | 800 lb | 12 in | 42 in | 143 in | 42 in | Cotterman | 3UU89 * | 5FZC0 * | 5FZA1 * |
| 150 in | 192 in | 15 | 800 lb | 24 in | 42 in | 155 in | 42 in | Cotterman | 20Z471 * | 20Z470 * | 20Z469 * |
| 56° Climbing Angle | | | | | | | | | | | |
| 60 in | 96 in | 6 | 600 lb | 10 in | 35 in | 50 in | 36 in | Tri-Arc | 2NJV4 * | 2NJW2 * | — |
| 70 in | 106 in | 7 | 600 lb | 10 in | 35 in | 57 in | 36 in | Tri-Arc | 2NJV5 * | 2NJW3 * | — |
| 80 in | 116 in | 8 | 600 lb | 10 in | 35 in | 64 in | 36 in | Tri-Arc | 2NJV6 * | 2NJW4 * | — |
| 90 in | 126 in | 9 | 600 lb | 10 in | 35 in | 69 in | 36 in | Tri-Arc | 2NJV7 * | 2NJW5 * | — |
| 100 in | 136 in | 10 | 600 lb | 10 in | 35 in | 76 in | 36 in | Tri-Arc | 2NJV8 * | 2NJW6 * | — |
| 110 in | 146 in | 11 | 600 lb | 10 in | 35 in | 83 in | 36 in | Tri-Arc | 2NJV9 * | 2NJW7 * | — |
| 120 in | 156 in | 12 | 600 lb | 10 in | 35 in | 90 in | 36 in | Tri-Arc | 2NJW1 * | 2NJW8 * | — |
| Platform Height | Overall Height | No. of Steps | Load Capacity | Platform Depth | Bottom Width | Base Depth | Handrail Height | Brand | SERRATED Item No. | PERFORATED Item No. | |
| 59° Climbing Angle | | | | | | | | | | | |
| 50 in | 92 in | 5 | 1,000 lb | 24 in | 37 in | 56 in | 42 in | Cotterman | 46C330 | 46C338 | |
| 60 in | 102 in | 6 | 1,000 lb | 24 in | 37 in | 62 in | 42 in | Cotterman | 46C331 | 46C339 | |
| 70 in | 112 in | 7 | 1,000 lb | 24 in | 37 in | 68 in | 42 in | Cotterman | 46C332 | 46C340 | |
| 80 in | 122 in | 8 | 1,000 lb | 24 in | 37 in | 74 in | 42 in | Cotterman | 46C333 | 46C341 | |
| 90 in | 132 in | 9 | 1,000 lb | 24 in | 37 in | 80 in | 42 in | Cotterman | 46C334 | 46C342 | |
| 100 in | 142 in | 10 | 1,000 lb | 24 in | 37 in | 86 in | 42 in | Cotterman | 46C335 | 46C343 | |
| 110 in | 152 in | 11 | 1,000 lb | 24 in | 42 in | 92 in | 42 in | Cotterman | 46C336 | 46C344 | |
| 120 in | 162 in | 12 | 1,000 lb | 24 in | 42 in | 98 in | 42 in | Cotterman | 46C337 | 46C345 | |

* Ladders for use in California will be modified to comply with California OSHA Standards.